

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
27 January 2005 (27.01.2005)

PCT

(10) International Publication Number  
**WO 2005/008627 A1**

(51) International Patent Classification<sup>7</sup>: **G10L 15/22**,  
15/26

(21) International Application Number:  
PCT/TB2004/051132

(22) International Filing Date: 6 July 2004 (06.07.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
03102229.6 18 July 2003 (18.07.2003) EP

(71) Applicant (for DE only): **PHILIPS INTELLECTUAL  
PROPERTY & STANDARDS GMBH** [DE/DE]; Stein-  
damm 94, 20099 Hamburg (DE).

(71) Applicant (for all designated States except DE, US):  
**KONINKLIJKE PHILIPS ELECTRONICS N. V.**  
[NL/NL]; Groenewoudseweg 1, NL-5621 BA Eindhoven  
(NL).

(72) Inventor; and

(75) Inventor/Applicant (for US only): **SCHOLL, Holger**  
[DE/DE]; c/o Philips Intellectual Property & Standards  
GmbH, Weissshausstr. 2, 52066 Aachen (DE).


(74) Agent: **MEYER, Michael**; Philips Intellectual Property &  
Standards GmbH, Weissshausstr. 2, 52066 Aachen (DE).

(81) Designated States (unless otherwise indicated, for every  
kind of national protection available): AE, AG, AL, AM,  
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,  
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,  
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,  
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,  
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,  
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,  
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,  
ZW.

(84) Designated States (unless otherwise indicated, for every  
kind of regional protection available): ARIPO (BW, GH,

[Continued on next page]

(54) Title: METHOD OF CONTROLLING A DIALOGING PROCESS



(57) Abstract: A method of controlling a dialoging process is described in which a current situation parameter (syp, mi, si) is automatically determined and in which the control of the dialoging process takes place as a function of the situation parameter (syp, mi, si) in such a way that the dialoging process is adapted to the current situation.

WO 2005/008627 A1



GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

**Published:**

— with international search report

— before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

## Method of controlling a dialoging process

The invention relates to a method of controlling a dialoging process, particularly in the context of a speech-controlled application, and to a corresponding dialoging system.

5

Recently, developments in the field of the man-machine interface have meant that the operation of technical devices is increasingly being performed by a dialog between the technical device and the user of the device. In this way, it is in particular known for a navigation system to be operated by having the navigation system address questions or  
10 commands to the user of the navigation system by the output of synthesized speech, and by having the user engage in a dialog with the navigation system by speaking commands or questions. Also known however are operating dialogs that are not based on speech. In this way, almost every mobile telephone is, for example, nowadays set by means of an operating dialog that is based on the display of options on a graphics display belonging to the mobile  
15 telephone, and on the selection of one of the options as a result of the appropriate key being pressed by the user.

Operating dialogs of this kind between man and machine bring with them the disadvantage that, unlike dialogs that are carried on between human beings, the process followed in them is always the same. For a long time, no provision was made for any  
20 adaptation to the surroundings or to the user. To overcome this disadvantage, approaches to a solution have now been conceived and even implemented in practice. In this way, there are known operating dialogs in which, in a first operating step, the user makes an input to say whether he is using the device being operated for the first time or whether he is already familiar with the way in which the device is operated. On the basis of this first input by the  
25 user, the continuation of the operating dialog is adapted to the experience the user has had, by for example at first not even offering the first-time user, for him to select, certain options that are not absolutely necessary for the operation of the device, but doing this for an experienced user. Another approach to a solution is oriented in an entirely different direction, namely to adapting only the dialog output to the surroundings. For this purpose, it is for example known

for ambient noise to be determined and, as a part of an operating dialog, for the volume of a speech output to be adapted to the ambient noise in such a way that the volume of the output is high when the volume of the ambient noise is high, and vice-versa.

Although these known solutions considerably improve the operating dialog  
5 between man and machine, in practice they still do not give satisfactory results, particularly in comparison with a man-man dialog.

It is therefore an object of the present invention to specify a method of  
10 controlling a dialoging process that enables reliable communication to take place between a technical device and a user of the device.

This object is achieved by a method of the kind stated in the opening paragraph in which a current situation parameter is determined, and in which the control of the dialoging process takes place as a function of the situation parameter in such a way that  
15 the dialoging process is adapted to the current situation. The dependent claims relate in the respective cases to advantageous embodiments and refinements of the invention.

The invention is based in this case firstly on the idea of automatically sensing, continuously or at fixed or varying intervals of time, the current situation in which the dialog to be controlled is taking place. In particular, the dialoging process may be constantly  
20 adapted to the current situation. For this purpose, one or more situation parameters are determined that are characteristic of the current situation as far as the dialog to be controlled is concerned.

Depending on the dialog that is to be controlled or on the application in which the dialog to be controlled is taking place, there are an enormous variety of situation  
25 parameters that may be considered. Preferably however, it is one or more of the following situation parameters that are determined: locational information, location co-ordinates, time information, time of day, image information, audio information, video information, temperature information, lighting information (such as, for example, brightness of outside lighting), information on the surroundings (such as, for example, ambient noise), information  
30 on the user (such as, for example, blood pressure, pulse rate, rate of perspiration, how much the user is moving, etc.), speed information, driving situation information (such as, for example, acceleration information, inclination information, braking system information, steering system information, accelerator pedal information, brake anti-locking system information, ESP (electronic stability system) information, headlight information, traffic

density, road surface characteristics, etc.) and/or social activity indicators (such as, for example, the number of other people in the surrounding area, amount of interaction).

In addition or as an alternative to these situation parameters, provision is preferably made for situation parameters to be formed by system parameters of the dialoging system itself or of a part of the dialoging system, such as, for example, those of a speech recognition system. In this way, the following speech recognition parameters too may be used as situation parameters: signal-to-noise ratio (SNR), speed of articulation, tonal or linguistic stress indicators, degrees of confidence achieved in the recognition, previous utterances by the user, number of the system's semantic concepts open at the same time in a dialoging process, proportion of expletives in the user's speech and/or speech-impact indicators (such as, for example, the number of hesitations, etc.). What is achieved in this way is that the current situation can be sensed at little additional cost and complication, because what is used as a situation parameter is a system parameter that is being generated anyway in the context of the dialoging process for other purposes.

As a function of the situation parameter or parameters that is/are sensed, the dialoging process is then controlled in such a way that it is adapted to the current situation. A dialoging process may, for example, be defined by dialog steps in this case. The dialog steps may comprise dialog input steps (input by the user to the dialoging system) and/or dialog output steps (output from the dialoging system to the user). The adaptation of the dialoging process may, for example, be performed by changing the dialog steps themselves. The change to a dialog step will preferably be implemented as a change in the amount and/or nature of the information output in a dialog step, and/or in the options. In addition or as an alternative to changing the dialog steps themselves, it is also possible for the dialoging process to be adapted by changing the sequence of the dialog steps or by changing the dialog steps that are selected from a possible maximum set of dialog steps. To simplify a dialoging process in, for example, critical operating situations, the number of options offered in the individual dialog output steps may be reduced, or only options that are easy to grasp or that are essential for operation in the situation concerned may be displayed, and/or the options offered may be shown in such a way that they are particularly easy for the user to grasp. In addition or as an alternative to this, the dialog output steps performed will preferably be only the ones that are essential for operation in the situation concerned.

The invention gives particular advantages if it is embedded in a speech-controlled application that comprises speech recognition and speech output. This is because it is precisely in this environment that a man-machine dialog is possible in the most varied

situations and an adaptation to the current situation is particularly effective. In this way, a navigation system in a vehicle can, basically, be operated by speech both when the vehicle is stationary and while it is traveling along a freeway or motorway. However, travel along a freeway or motorway calls for greater attentiveness from the driver, and it is therefore  
5 advantageous for the dialoging process to be simplified in this situation. For this purpose, the language used in the dialog output steps may, for example, be simplified, by giving preference to the output of words whose meaning or sound is easy to understand, to defining options in a few words and/or to outputting questions that can be replied to by the user with simple answers such as "Yes" or "No". In this case, the speech recognition that is applied to  
10 the dialog input steps, i.e. to the spoken commands by the user, is preferably adapted to the current situation by causing the recognition to require a higher degree of reliability in critical situations than in non-critical situations, in order to avoid any mis-operation. In addition or as an alternative to this, the speech recognition that is applied to the dialog input steps is adapted to the options that were output in the preceding dialog output step, which options had  
15 been adapted to the situation, by causing it to expect spoken input information corresponding to the output step. So if, as a consequence of the dialoging process being adapted in a critical operating situation, a question that expects the answer "Yes" or "No" is output in a dialog output step, the speech recognition system is controlled in such a way that it preferably checks the input that follows from the user to see whether "Yes" or "No" is said.

20 When a speech control system is being used, what is preferably employed as a situation parameter is, in the way that has already been described above, a system parameter that characterizes the user's speech (a speech recognition parameter). For example, a high speed of articulation, speaking loudly, speech that is hard to understand and/or loud background noise may also be an indication of a critical situation.

25 A dialoging process in which automatic speech recognition is incorporated may, for example, be adapted to the current situation by causing the dialoging system to output a small vocabulary, short words and/or simple words in a critical situation and/or to use distinct, i.e. particularly clear, enunciation in such a situation. In addition or as an alternative to this, preference may be given in the output steps to outputting questions that  
30 require only a short answer. What was also found to be advantageous in preliminary investigations is for inputs detected by the speech recognition system that are particularly important in critical situations to be made subject to explicit verification by causing them to be output again for checking before they undergo any further processing. In non-critical or relaxed situations on the other hand, the speech recognition system or speech output can be

switched to a conversational mode in which the user can communicate with the system using a larger vocabulary and in which user inputs are, for example, verified only implicitly in subsequent dialog steps. Also, in critical situations for example, an automatic switch can be made to a mode of operation determined by the system in which the system dictates the precise course of a dialoging process and no changes are possible to it. In more relaxed situations on the other hand, the system may run in what is termed a "mixed initiative" mode of operation in which the user can also make inputs not asked for by the system on his own initiative. Unprompted inputs of this kind are understood by the system and if required the dialoging process is altered accordingly. Changes in the mode of operation of this kind are, for example, possible by adjusting the number of semantic concepts that are open during a dialog. The number of semantic concepts that are open is preferably reduced in critical situations, or if required operations may even proceed with only one semantic concept open.

To enable a dialoging situation to be sensed as comprehensively as possible, and to enable a dialoging process to be adapted stably and in a practical manner to the situation that is sensed with little cost and complication, investigations involving considerable expenditure have shown it to be particularly advantageous for a current situation profile to be determined as part of a situation classification on the basis of the situation parameter or parameters determined, and for the adaptation of the dialoging process to the current situation to be carried out on the basis of the situation profile that is determined. When use is in a vehicle, what may be provided as situation profiles are, for example, a "critical driving situation" a "non-critical driving situation" and a "parking situation". The situation profiles are preferably defined by applying logic "AND" or "OR" conditions respectively assigned to them to ranges of one or more situation parameters. In this way, a "critical driving situation" for example is found to exist if the speed is more than 100 km/h OR the level of acceleration is higher than a preset threshold level for acceleration. A "non-critical driving situation" is preferably found to exist if the speed is less than 100 km/h AND if the ambient noises are quiet. The "parking situation" can typically be defined by an engine that is switched off.

In addition or as an alternative to the "discrete" adaptation of the dialoging process to the current situation that has been described above (mapping of the current situation onto discrete situation profiles), provision is preferably made for a "continuous" adaptation of the dialoging process to the current situation (mapping of the current situation onto a continuous situation-related value), in which, when there are small changes in the current situation, the dialoging process too is changed only in steps of any desired small size.

For thus purpose, a current situation-related value that characterizes the current situation is determined from the situation parameter or parameters, by mathematical mapping for example. Preferably, the mathematical mapping is so defined in this case that the result is that a high situation-related value stands for a critical situation, whereas a low situation-related value stands for a non-critical situation. The speed of the synthesized speech that is output by a vehicle navigation system may, for example, be reduced linearly with the increase in the speed of the vehicle. What is used as a situation-related value in this case is only the speed of the vehicle. The result of combining the "discrete" adaptation with the "continuous" adaptation is an unsharp classification of situations that is particularly stable and user-friendly.

As a particular preference, provision is made for the dialoging process to be changed as a function of whether the situation that exists is a private one or, in contrast to this, a public one. A private situation may, for example, exist when the ambient noise is quiet whereas a public situation exists when the ambient noise is loud. Authentication of the user in a private situation, such as at home for example, may for example take place as part of a dialog step by the explicit uttering of a secret number. So that no private information has to be uttered in the course of a dialoging process in a public situation, such as, for example, on a bus or in a queue waiting to use a cash machine, the dialoging process is controlled in such a way that only a non-spoken input via a PIN pad or the like is asked for.

The invention also covers a dialoging system having a dialog input/output interface, having a situation parameter interface, and having a dialog controlling means that is so arranged that a current situation parameter is determined automatically and that the control of a dialoging process is performed in such a way, as a function of the situation parameter, that the dialoging process is adapted to the current situation. Via the situation parameter interface, the dialoging system may be connected in this case particularly to situation sensing means, such as, for example, sensor means or measuring means of various kinds. The dialoging system is preferably connected via the dialog input/output interface to an input means, such as, for example, a microphone or a keyboard, and/or to an output means, such as, for example, a loudspeaker or a display device. To prevent the dialoging system from having to process raw sensor data, further signal processing means or information treating means are provided between the interfaces and the situation sensing means or input/output means.

The invention also covers dialoging systems that are embodied as in the claims dependent on the method claim.



These and other aspects of the invention are apparent from and will be elucidated with reference to the embodiments described hereinafter.

5 In the drawings:

Fig. 1 is a simplified general arrangement drawing of a dialoging system.

Fig. 2 is a schematic representation of steps in a method of controlling a dialoging system.

To make things clearer, only the essential components of, in particular, the  
10 hardware configuration of the system has been shown in Fig. 1. It is clear that this system may also have all the other components that normally form part of dialoging systems, such as, for example, suitable connecting lines, amplifier means, controls or a display means.

15 Fig. 1 shows, as part of a dialoging system DS, a situation parameter interface PSS, via which the dialoging system DS is connected to sensor means S1 .... Sn and measuring means M1 ... Mm. The dialoging system DS is also connected via an input/output interface E/ASS to a loudspeaker LS and a microphone MIC. The dialoging system DS also has a situation assessing unit SA. To the situation assessing unit SA is fed the sensor data si  
20 from the sensor means S1 ... Sn and the measurement data mi from the measuring means M1 ... Mn, which data is incoming via the situation parameter interface PSS. Also fed to the situation assessing unit SA are speech recognition system parameters sysp, which are determined anyway as intermediate or final results as part of a speech control process.

On the basis of the situation parameters that have currently been determined  
25 (sensor data si, measurement data mi, speech recognition system parameters sysp), the current situation profile sp and in addition, for a more accurate assessment, a current situation-related value sw, are determined in the situation assessing unit SA and are passed on to a dialog controlling means DSTE that forms the heart of the dialoging system DS. Control parameters stp are then determined in the dialog controlling means DSTE on the  
30 basis of the situation profile that has been determined and/or the situation-related value that has been determined. The control parameters stp are passed on both to a dialog manager DM and also to the individual parts of a speech control system SSt. The speech control system SSt is implemented in this case by means of an automatic speech recognition unit ASR, a speech interpretation unit ASU, a language generating unit LG and a speech synthesizing

means SS. Via the input/output interface E/ASS, the speech synthesizing means SS is connected to the loudspeaker LS and the speech recognition unit ASR to the microphone MIC. The dialog manager organizes mainly the dialoging process, such as, for example, the selection and sequence of the input and output steps. As a result of the control parameters stp acting on the dialog manager DM, the dialoging process is adapted to the current situation. In addition to this, the dialoging process is also adapted to the current situation by the effects that the control parameters stp have on the parts ASR, ASU, LG and SS of the speech control system SSt.

The dialog manager DM, the dialog controlling means DSTE and/or the situation assessing means SA in particular may be formed, individually or together, by one or more program-controlled computer units and other circuit arrangements provided specifically for this purpose, whose programming is designed to perform the method according to the invention. For this purpose, the computer unit or units may be equipped with a processor means and a memory means. In the memory means may be stored not only the program data but also the definitions of various situation profiles sp and situation-related values sw and their mapping onto control parameters stp. Settings of the dialoging system DS that are made by the user of the dialoging system DS may also be stored in the storage means. As a supplement to this, information that is used to control the dialoging process or to interpret spoken inputs by the user may also be stored in databases provided specifically for this purpose, such as, for example, an application database ADB and a knowledge database WK, both of which the dialog manager DM may access.

There may also be provided in this case, as a part of this computer unit or units or separately therefrom, other information-processing means that for example preprocess the measured values mi, the sensor data si or the speech recognition system parameters sysp or apply further processing to the control parameters stp.

By reference to Fig. 2, there will now be elucidated an illustrative course followed by a method by which the dialoging process of a speech-controlled vehicle navigation system is adapted to the current situation.

At the beginning, let the vehicle be situated in the acceleration lane of a freeway or motorway. In a first step, to give situation parameters, the speed v1 of the vehicle is measured, the acceleration a1 of the vehicle is sensed by an acceleration sensor, and the background noise g1 is determined as a speech recognition system parameter as part of the speech recognition process. These situation parameters v1, a1, g1 are fed to the situation assessing unit. Because of the high speed v1 of the vehicle, the high acceleration a1 and the

loud engine noise  $g_1$ , a critical situation is found to exist as a situation profile  $sp_1$ . Also, from the three incoming situation parameters  $v_1$ ,  $a_1$ ,  $g_1$ , a high situation-related value  $sw_1$  is determined that reflects the fact that all three of the situation parameters  $v_1$ ,  $a_1$ ,  $g_1$  are themselves particularly high for a critical situation.

5           The situation profile  $sp_1$  and the situation-related value  $sw_1$  are then mapped onto a control parameter  $stp_1$  or a set of control parameters, which is/are then fed to the dialog manager and the speech recognition system. As a result of the control parameter  $stp_1$  being processed in the dialog manager and the speech recognition system, the dialoging process is adapted to the current situation. Because of the critical situation that has been  
10 found to exist, the dialog between the navigation system and the user for example is set in such a way that the navigation system outputs only easily comprehensible information to which the user can respond by uttering the words "Yes" or "No".

          In a second step, let the vehicle be situated in a quiet parking space with the engine switched off. Once again, to give situation parameters, the speed  $v_2$  is measured, the  
15 acceleration  $a_2$  is sensed, and the background noise  $g_2$  is determined as a speech recognition system parameter. The situation parameters  $v_2$ ,  $a_2$ ,  $g_2$  are once again fed to the situation assessing unit and what is now found to exist is an non-critical situation or even a "Parking situation". Also, a low situation-related value  $sw_2$ , which reflects the fact that the vehicle is not only standing still but is also doing so in particularly quiet surroundings, is determined  
20 from the three incoming situation parameters  $v_2$ ,  $a_2$ ,  $g_2$ .

          The situation profile  $sp_2$  and the situation-related value  $sw_2$  are then once again mapped onto a control parameter,  $stp_2$  in this case, or a set of control parameters, which is/are then fed to the dialog manager and the speech recognition system. As a result of the control parameter  $stp_2$  being processed in the dialog manager and the speech recognition  
25 system, the dialoging process is once again adapted to the current situation. Because of the "Parking situation" that has been found to exist, the dialog between the navigation system and the user for example is set in such a way that, as part of a dialoging process, the navigation system even outputs information that is relatively difficult to understand and that conveys a relatively complex message, to which the user responds even with answers whose meaning is  
30 more involved than a simple "Yes" or "No".

          Finally, it will again be pointed out that the systems and methods that are shown in the Figures and described in the description are merely illustrative embodiments that can be varied to a wide extent by the man skilled in the art without thereby exceeding the scope of the invention. In this way, a dialoging system that includes automatic speech

recognition was described by reference to the Figures. In addition or as an alternative to this, the dialoging system may however also include a display means, such as a graphic display, and controls, such as a keyboard or a touch-screen. A dialoging system according to the invention may also be incorporated in a mobile telephone, an electronic notebook, a portable  
5 electronic device used for home entertainment, such as an audio/video player for example, or in a household appliance such as a washing machine or a cooker, or in an automatic teller machine.

For the sake of completeness, it should also be pointed out that the use of the indefinite article "a" or "an" does not rule out the possibility of the feature concerned being  
10 present more than once and the use of the term "comprise" does not rule out the possibility of there being other items or steps.

## CLAIMS:

1.           A method of controlling a dialoging process in which
  - a current situation parameter (sysp, mi, si) is automatically determined and
  - the control of the dialoging process takes place as a function of the situation parameter (sysp, mi, si) in such a way that the dialoging process is adapted to the current situation.
- 5           2.           A method as claimed in claim 1, characterized in that the dialoging process is embedded in the framework of a speech-controlled application and in that an automatic speech recognition unit (ASR) is used in the dialoging process.
- 10          3.           A method as claimed in either of the foregoing claims, characterized in that a speech synthesizing means (SS) is used in the dialoging process.
4.           A method as claimed in any of the foregoing claims, characterized in that a current situation profile (sp) is determined on the basis of the situation parameter (sysp, mi,  
15          si) determined and in that the control of the dialoging process takes place as a function of situation profile (sp) in such a way that the dialoging process is adapted to the current situation.
5.           A method as claimed in claim 4, characterized in that various situation profiles  
20          (sp) are assigned to various ranges of situation parameters and in that what is determined as the current situation profile (sp) is that situation profile (sp) that is assigned to the range of situation parameters in which the situation parameter (sysp, mi, si) determined lies.
6.           A method as claimed in any of the foregoing claims, characterized in that a  
25          current situation-related value (sw) is determined from the situation parameter (sysp, mi, si) determined and in that the control of the dialoging process takes place as a function of the situation-related value (sw) in such a way that the dialoging process is adapted to the current situation.

7. A method as claimed in any of the foregoing claims, characterized in that what is used as a situation parameter (sysp, mi, si) is a system parameter (sysp) that is generated anyway in the context of the dialoging process for some other purpose.

5 8. A method as claimed in claim 7, characterized in that a speech recognition system parameter that is generated as part of automatic speech recognition (ASR) is used as a situation parameter (sysp).

9. A method as claimed in any of the foregoing claims, characterized in that the  
10 control of the dialoging process takes place as a function of a situation parameter (sysp, mi, si) in such a way that user authentication in a private situation calls for the input of a user data object in a way in which the input is not required in a public situation.

10. A dialoging system (DS) having a dialog input/output interface (E/ASS), a  
15 situation parameter interface (PSS), and a dialog controlling means (DSTE) that is so arranged that:

- a current situation parameter (sysp, mi, si) is automatically determined and
- the control of the dialoging process takes place as a function of the situation parameter (sysp, mi, si) in such a way that the dialoging process is adapted to the current situation.

20

11. A dialoging system (DS) as claimed in claim 10, characterized by a sensor means (S1 ... Sn) connected to the situation parameter interface (PSS) and/or a measuring means (M1 ... Mm) connected to the situation parameter interface (PSS), for determining sensor data (si) and measurement data (mi) respectively.

1/2




FIG. 1

2/2




FIG. 2



## INTERNATIONAL SEARCH REPORT

tional Application No

PCT/IB2004/051132

A. CLASSIFICATION OF SUBJECT MATTER  
IPC 7 G10L15/22 G10L15/26

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 G10L

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data, PAJ, INSPEC

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	<p>PORZEL R, STRUBE M: "Towards Context-adaptive Natural Language Processing Systems" INT. SYMPOSIUMPUTATIONAL LINGUISTICS FOR THE NEW MILLENIUM, 2000, pages 1-12, XP002298294 HEIDELBERG, GERMANY page 6, paragraph 5 - page 7, paragraph 1 page 9, paragraph 1</p> <p>----- -/--</p>	1-11

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

## \* Special categories of cited documents:

\*A\* document defining the general state of the art which is not considered to be of particular relevance

\*E\* earlier document but published on or after the international filing date

\*L\* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

\*O\* document referring to an oral disclosure, use, exhibition or other means

\*P\* document published prior to the international filing date but later than the priority date claimed

\*T\* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

\*X\* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

\*Y\* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

\*Z\* document member of the same patent family

Date of the actual completion of the international search

29 September 2004

Date of mailing of the international search report

28/12/2004

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax: (+31-70) 340-3016

Authorized officer

Burchett, S

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT		
Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	BRÜHLER D, MINKER W, HÄUBLER J, KRÜGER S: "Flexible Multimodal Human-Machine Interaction in Mobile Environments" ECAI WORKSHOP ON ARTIFICIAL INTELLIGENCE IN MOBILE SYSTEMS AIMS 2002, July 2002 (2002-07), pages 1-5, XP002298295 LYON, FRANCE the whole document	
A	STOEBER K ET AL: "SPEECH SYNTHESIS USING MULTILEVEL SELECTION AND CONCATENATION OF UNITS FROM LARGE SPEECH CORPORA" VERBMOBIL: FOUNDATIONS OF SPEECH TRANSLATION, XX, XX, 2000, pages 519-534, XP008025703 page 532 - page 533	
A	EP 1 176 489 A (DEW ENGINEERING AND DEV LTD) 30 January 2002 (2002-01-30) abstract	9
A	EP 1 085 501 A (CANON KABUSHIKI KAISHA) 21 March 2001 (2001-03-21) the whole document	
A	US 2002/065651 A1 (PHILIPS PETRA ET AL) 30 May 2002 (2002-05-30) the whole document	
A	WO 02/35518 A (TSUNASHIMA NORIYUKI ; KENWOOD CORP (JP)) 2 May 2002 (2002-05-02) abstract	

# INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/IB2004/051132

Patent document cited in search report		Publication date		Patent family member(s)		Publication date
EP 1176489	A	30-01-2002	CA	2317259 A1		25-01-2002
			EP	1176489 A2		30-01-2002
			TW	539981 B		01-07-2003
EP 1085501	A	21-03-2001	JP	2001086239 A		30-03-2001
			EP	1085501 A2		21-03-2001
US 2002065651	A1	30-05-2002	DE	10046359 A1		28-03-2002
			EP	1191517 A2		27-03-2002
			JP	2002162993 A		07-06-2002
WO 0235518	A	02-05-2002	JP	2002132290 A		09-05-2002
			WO	0235518 A1		02-05-2002